

12

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2002086346 A**

(43) Date of publication of application: **26.03.02**

(51) Int. Cl

**B24B 37/00**  
**C03C 19/00**  
**C08G 61/06**  
**C08J 5/14**  
**C08K 5/00**  
**C08L 65/00**  
**G02F 1/13**  
**G02F 1/1333**  
**G11B 5/84**  
**G11B 7/26**  
**H01L 21/304**

(21) Application number: **2000276319**

(22) Date of filing: **12.09.00**

(71) Applicant: **TEIJIN METON KK**

(72) Inventor:  
**YAMADA KENKO**  
**YOSHIDA EIJI**  
**YOSHIKIYO NOBUO**

(54) **POLISHING PAD**

(57) Abstract:

**PROBLEM TO BE SOLVED:** To provide a polishing pad having an appropriate hardness, good durability, less water absorptiveness, and capable of being molded into various shapes easily.

**SOLUTION:** The polishing pad for the surface of a substance is formed from a resin consisting of an open

ring polymer prepared through metathesis polymerization of ring-form olefin, wherein the resin has a thermal deformation temperature of 90-135°C, a compression modulus of elasticity of 980-2940 MPa, and a water absorptiveness of 0.01-0.25 wt.%, and the resultant pad has an appropriate hardness, good durability and less water absorptiveness, and is unlikely to damage the surface of the substance to be polished.

**COPYRIGHT: (C)2002,JPO**